



Chainstaylength versus Beltlength



Külfalstr. 18
 31093 Lübbrechtsen
 Germany
 Tel: +49 5185 60266-50
 Fax: +49 5185 957 192
 Info@carbondrive.net
 www.carbondrive.net

Date: 19.04.2010

Beltlength in (mm)	Beltlength in number of teeth	Front sprocket number of teeth	Front sprocket nominal diameter (mm)	Rear sprocket number of teeth	Rear sprocket nominal diameter (mm)	Ratio	Comparison to a half inch chaindrive	Ratio	Chainstaylength; +/- 7,5(mm) for tension purpose
1298	118	60	210,08	32	112,05	1,88	52-28	1,86	392,94
1298	118	60	210,08	28	98,04	2,14	52-24	2,17	403,11
1298	118	55	192,58	32	112,05	1,72	48-28	1,71	407,76
1298	118	60	210,08	25	87,54	2,4	52-21	2,47	410,68
1298	118	60	210,08	24	84,03	2,5	52-21	2,47	413,19
1298	118	55	192,58	28	98,04	1,96	48-24	2	418,08
1298	118	60	210,08	22	77,03	2,73	52-19	2,74	418,21
1298	118	60	210,08	21	73,53	2,86	48-17	2,82	420,71
1298	118	50	175,07	32	112,05	1,56	44-28	1,57	422,32
1298	118	60	210,08	20	70,03	3	52-17	3,06	423,21
1298	118	60	210,08	19	66,53	3,16	52-16	3,25	425,7
1298	118	55	192,58	25	87,54	2,2	48-21	2,29	425,76
1298	118	55	192,58	24	84,03	2,29	48-21	2,29	428,31
1298	118	50	175,07	28	98,04	1,79	44-24	1,83	432,79
1298	118	55	192,58	22	77,03	2,5	48-19	2,53	433,4
1298	118	46	161,06	32	112,05	1,44	40-28	1,43	433,81
1298	118	55	192,58	21	73,53	2,62	44-17	2,59	435,94
1298	118	55	192,58	20	70,03	2,75	44-16	2,75	438,47
1298	118	50	175,07	25	87,54	2	44-21	2,09	440,58
1298	118	55	192,58	19	66,53	2,89	48-16	3	441
1298	118	50	175,07	24	84,03	2,08	44-21	2,09	443,16
1298	118	46	161,06	28	98,04	1,64	40-24	1,67	444,38
1298	118	50	175,07	22	77,03	2,27	44-19	2,32	448,32
1298	118	50	175,07	21	73,53	2,38	44-19	2,32	450,89
1298	118	46	161,06	25	87,54	1,84	40-21	1,9	452,26
1298	118	50	175,07	20	70,03	2,5	44-17	2,59	453,46
1298	118	46	161,06	24	84,03	1,92	40-21	1,9	454,87
1298	118	50	175,07	19	66,53	2,63	44-16	2,75	456,02
1298	118	46	161,06	22	77,03	2,09	40-19	2,11	460,08
1298	118	46	161,06	21	73,53	2,19	40-19	2,11	462,68
1298	118	46	161,06	20	70,03	2,3	40-17	2,35	465,27
1298	118	46	161,06	19	66,53	2,42	40-16	2,5	467,86